

Data Sheet FUJITSU Thin Client FUTRO S9010

Flexible and Powerful Thin Client

The FUTRO S9010 is a future-ready, flexible Thin Client device with an optimal mix of industry leading OS and Thin Client device management consoles, ISV protocols and highly flexible hardware options helping you provide secure computing and full productivity options for your employees for creating the workplace of the future.

eLux RP 6 Thin Client OS and Scout Enterprise Management Suite® 15

Enables you to save on costs upfront and keep your IT infrastructure secure and up-to-date with continuous security patch releases

 Unicon offers a flexible licensing model that includes the eLux OS and Scout Enterprise Management Suite with long term support for the latest updates

Enterprise-grade Security

Enables you to provide a secure end-point device that helps prevent unauthorized access to sensitive enterprise data

 Centralized administration and granular access controls coupled with built-in BIOS Security, Write Filter Protection and Kensington lock support

Full productivity

Enables your workforce to be more productive with UC&C and multiple display options and multiple connectivity options that can get work done faster and more efficiently

UC&C ready with multi-monitor support for up to five 4K displays and ideal mix of modern (Type-C) and legacy interfaces

Investment Protection

Helps you run your Thin Clients on the latest and most secure versions of the eLux RP and Scout Enterprise Management Suite

 Scout Subscription helps provide perpetual updates and upgrades to eLux RP 6 and Scout Enterprise Management Suite 15

Lean IT ready

Helps you modernize your workspaces by promoting a Lean IT, clean desk and ergonomic approach without compromising on performance

■ Small footprint, Fanless design, Smart Card option and optimal Performance-to-Power ratio









■ Windows 10

Page 1 / 6 www.fujitsu.com/emeia/FUTRO

Technical details Components

Memory modules	4 GB (1 module(s) 4 GB) DDR4, 2,400 MT/s, SO DIMM	
	8 GB (1 module(s) 8 GB) DDR4, 2,400 MT/s, SO DIMM	
Graphics	NVIDIA® Quadro® P400 , 2 GB	
•	MiniDP to DP Adapter Cable	
	DP to DVI-D (single link) Adapter Cable	
	Display Port to VGA Adapter	
Characa (inhernal)	SSD SATA, 128 GB, M.2 module, Flash drive (TLC technology), 220 TBW*	
Storage (internal)		
<u> </u>	SSD SATA, 64 GB, M.2 module, Flash drive (TLC technology), 110 TBW*	
Storage notes	Important Notice for M.2 Module Use: Predefined by NAND-Flash-Technology the device only supports a defined maximum number of Terabytes written.	
	Any and all warranty for such devices is limited to this maximum Terabytes written. Please notice the section	
	"restricted warranty" in our warranty book.	
	Fujitsu therefore strongly recommends to activate the write filter of the mSATA module once the configuration is	
	finished. This activation ensures the durability of the flash module and is also mandatory to ensure a highest level	
	of IT security (e.g. against virus attacks). In case of a need to enable further write cycles the write filter can then be deactivated again at any time.	
	*Terabytes written (TBW) calculated based on JESD-219A SSD Client workload	
	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.	
Interface add on cards/components (optional)		
	PCIe Riser	
	Internal speaker	
	Intel® WI-FI 6 AX200	
	Parallel Port	
	Dual serial card PCIe x1	
	USB 3.1 (gen2) Type-C PCle x 4	
	USB 3.1 (gen1) Type-C	
	2nd LAN/Power-over-Ethernet module, IEEE802.3at (max. 25.5W system power)	
Base unit	FUTRO S9010	
Operating system and software (Linux)		
Operating system	eLux® RP	
Notes	eLux® is a hardware-independent operating system for cloud computing environments. eLux ensures hardware	
. Total	independence and migration ability. An existing license can simply be transferred via Scout Enterprise whenever the	
	hardware is upgraded. New updates and upgrades are always built modular – only the changed parts (delta) of the	
	software are transferred to the device and implemented into the existing installation. Software updates and upgrades are available around the clock at myelux.com.	
Functions	eLux® RP 6	
Tunctions	Citrix Receiver	
	VMware® Horizon Client	
	Updates and optional software packages are available at www.myelux.com	
Manageability	Scout Enterprise, flash memory management, embedded operating system update and system monitoring,	
	managing devices by location, group or user, individual operating system composition with ELIAS (eLux and Scout Enterprise Management Suite license required)	
Operating system and software (Windo	ws 10 loT)	
Operating system	Windows® 10 IoT Enterprise 2019 LTSC	
Notes	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10	
	releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSL	
	Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at	
	http://support.ts.fujitsu.com.	

Page 2 / 6 www.fujitsu.com/emeia/FUTRO

Operating system and software (Windows 10 IoT)

Operating system and software (Window	ws 10 loT)					
Functions	Internet Explorer Citrix Receiver VMware® Horizon Client					
Mainboard						
Mainboard type	D3543-A2					
Formfactor	miniITX					
Processor	Intel® Pentium® Silver J5040 (Quad Core, 2.0 GHz, up to 3.2 GHz, Intel® UHD Graphics 605) (,)					
Memory slots	2 SO DIMM (DDR4, 2400 MHz)					
Supported capacity RAM (max.)	16 GB					
LAN	Built-in 10/100/1,000 MBit/s Realtek RTL8111G					
BIOS features	BIOS Flash EPROM update by software Recovery BIOS Unified Extensible Firmware Interface (UEFI)					
Audio type	On board					
Audio codec	Realtek ALC671					
Interfaces						
Audio: line-in	1					
Audio: line-out	1					
Front audio: microphone	1					
Front audio: headphone	1					
USB 2.0 total	4 rear					
USB 3.1 Gen1 (USB 3.0) total	2 front + 1x Type-C rear as option					
USB front	2					
USB rear	4 + 1 (optional)					
USB internal	1 pin header (2x USB 2.0)					
DisplayPort	2x DP1.2a					
Serial (RS-232)	2					
Mouse / Keyboard (PS/2)	2					
Ethernet (RJ-45)	1					
Parallel	1x as option					
Graphics on board						
Graphics brand name	Intel® UHD Graphics 605					
Graphics color depth	32 bit colors					
Shared video memory	up to 1.5 GB					
TFT resolution (DisplayPort)	up to 4,096 x 2,160 @ 60Hz					
Graphics features	DirectX® 12 OpenGL® 4.4 Open CL® 1.2 OpenGL® ES 3.1 Vulkan™					
Graphics notes	Graphics resolution and features depending on operating system and management solution. Three displays up to 2560 x 1440 pixels are supported via Daisy Chain (display 1 at DisplayPort 1, display 2 at DisplayPort 2, display 3 via Daisy Chain at display 1 or 2).					
Electrical values						
Power consumption long idle	10 W					
Power consumption sleep mode power	1.14 W (WoL enabled)					
Power consumption off mode power	0.2 W (WoL disabled)					
Rated voltage range	100 V - 240 V (AC Input)					
Rated frequency range	50 Hz - 60 Hz					
Operating voltage range	100 V - 240 V (AC Input)					
Operating line frequency range	50 Hz - 60 Hz					

Page 3 / 6 www.fujitsu.com/emeia/FUTRO

Dimensions / Weight / Environmental					
Dimension with stand (W x D x H)	90 x 193 x 261 mm				
Dimensions (W x D x H)	52 x 193 x 250 mm				
Dimension notes	Dimensions with WiFi w/o stand (W x D x H): 58 x 193 x 250 mm				
Operating position	Vertical / horizontal				
Weight	1048 g				
Weight notes	Actual weight may vary depending on configuration				
Operating ambient temperature	10 - 35 ℃				
Operating relative humidity	5 - 85 % (relative humidity)				
Compliance					
Product	FUTRO S9010				
Model	TCS				
Germany	GS in progress				
Europe	CE				
USA/Canada	FCC part 15B (Class B) and part 15C/E (depending on wireless configuration)				
Global	ENERGY STAR® 8.0 compliant EPEAT® Bronze (dedicated regions)				
India	BIS in progress				
Russia	EAC in progress				
China	CCC in progress				
Australia/New Zealand	RCM				
Compliance notes	Energy Star compliance may vary depending on actual configuration Product Name maybe followed by suffixes				
Compliance link	https://sp.ts.fujitsu.com/sites/certificates				
Security					
Physical Security	Kensington Lock support Intrusion switch				
System and BIOS Security	Trusted Platform Module (TPM 2.0), optional without TPM User and supervisor BIOS password				
User Security	Access protection via internal SmartCard reader (optional)				
Warranty					
Warranty period	2 years (depending on country)				
Warranty type	Bring-In / Onsite Service (for countries within region EMEIA, for all other countries depending on local regulations)				
Warranty Terms & Conditions Product Support Services - the perfect of	http://www.fujitsu.com/warranty extension				
Recommended Service	9x5, Onsite Response Time: Next Business Day				
Spare Parts availability	5 years after end of product life				
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/				

Recommended Accessories

Power over Ethernet (PoE) module	PoE modules enable the passing of electric power along with data via single Ethernet cable to devices such as FUTRO Thin Clients.	Order Code: S26361-F3466-E4
SmartCard Reader USB Internal	The Fujitsu SmartCard Reader USB Internal allows you to add SmartCard functionality to your FUTRO Thin Client. It provides an ideal platform for Public Key Infrastructure (PKI) applications, digital signature as well as SmartCard based authentication and access protection.	Order Code: S26361-F1260-E808
VESA Subadapter Velcro® strap for FUJITSU FUTRO Thin Clients	To mount the FUTRO system at rear side of the monitor. Contents: Subadapter, screws, bolts. Please check the compatibility of the monitor.	Order Code: S26361-F2601-L200

Page 4 / 6 www.fujitsu.com/emeia/FUTRO

VESA Mounting Kit for height adjusting FUJITSU Displays		VESA Mounting Kit to fix FUTRO S540, FUTRO S740, FUTRO S5010, FUTRO S7010 Thin Clients behind height adjustable FUJITSU displays of 8th and 9th generation	Order Code: S26361-F2601-L523
VESA Kit no Sub adapter for FUTRO S720, S930, S940		VESA Kit no Sub adapter for mounting FUTRO S720, FUTRO S930 and FUTRO S940 Thin Clients behind a monitor.	Order Code: S26361-F2601-L527
eLux® RP & Scout Enterprise Management Suite®	SCOUT enterprise eLUX° RP	Scout Enterprise Management Suite® ensures scalability, high availability and enabling the management of an unlimited number of Thin Clients and PCs with eLux® OS or Windows operating systems. eLux OS is an open, hardware agnostic operating system designed for cloud end points such as Thin Clients with a modular design, offering easy licensing options and migration alternatives.	Order Code: S26361-F2727-L801

Page 5 / 6 www.fujitsu.com/emeia/FUTRO

More information

Fujitsu products, solutions & services

In addition to FUJITSU Thin Client FUTRO S9010, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Thin Client FUTRO S9010, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/FUTRO

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at http://www.fujitsu.com/global/about/environment



Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html

Copyright 2020 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2020-05-25 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2020 Fujitsu Technology Solutions GmbH