Fujitsu recommends Windows 10 Pro for business.



# Data Sheet FUJITSU Tablet LIFEBOOK U9311X

### World's Lightest Convertible With A Pen

Available in red and black, the FUJITSU Tablet LIFEBOOK U9311X is a lightweight 360-degree foldable device. All-day battery runtime and global LTE ensure highest productivity in any place, while security features such as the integrated PalmSecure™ sensor keep your business data protected. Powerful performance and full connectivity with Intel® Thunderbolt™ 4 offer you best-in-class user experience.

### Ultra-slim and lightweight Convertible

The very slim and light housing make it very comfortable to carry the device. Thanks to its 360° foldability, it can be immediately turned from a Notebook to a Tablet – and back.

- Available in red or black
- Weighing from 1 kg with a robust magnesium housing
- Durability is MIL-STD-810H tested
- Intel® Iris® Xe Graphics

### Security at its best

No compromises in security and data protection – the integrated PalmSecure™ sensor turns your unique palm vein pattern into your personal key.

- PalmSecure™
- Fingerprint & Full HD IR Camera supporting Windows Hello (secureBIO)
- SmartCard reader
- Kensington Lock support

### Excellent connectivity and usability

Newest interfaces and convenient features. All ports are full-sized – even the LAN port. No adapters, that can be lost and cause additional costs, needed.

- Complete set of full-sized interfaces: HDMI, LAN and USB Type-C with Intel® Thunderbolt™ 4
- 13.3 inch FHD anti-glare touch display with pen input
- Pen garage with inductive charging function
- 5 MP rear camera

### Convenient mobility supporting usage on the go

Highest productivity on business trips without empty batteries or waste of time

- All-day battery runtime offers you the exceptional mobility that you need when on the move
- Anytime USB charging functionality for your peripheral devices, even when the system is turned off
- Always connected and instantly ready















## Components

Base unit	LIFEBOOK U9311X black	LIFEBOOK U9311X red	
Operating systems			
Operating system pre-installed	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home	Windows 10 Pro. Fujitsu recommends Windows 10 Pro for business. Windows 10 Home	
Operating system compatible	Windows 10	Windows 10	
Operating system notes	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support. ts.fujitsu.com.	Windows 10 Support: After the end of the product life FUJITSU will continue to test and support all upcoming Window 10 releases for a period of maximum 5 years – depending on the available extension of hardware services through FUJITSU Warranty top ups. For details please see "FUJITSU Service Statement for Windows 10 Semi-Annual-Channel Support" at http://support. ts.fujitsu.com.	
Processor	Intel® Core™ i7-1185G7 processor (4 Cores / 8 Threads)		
	Intel® Core™ i5-1145G7 processor (4 Cores / 8 Threads)		
	Intel® Core™ i5-1135G7 processor (4 Cores / 8 Threads) *		
	*Processor only for retail, SMB, education and governmen	t	
Memory	8 GB onboard Memory LPDDR4 16 GB onboard Memory LPDDR4 32 GB onboard Memory LPDDR4 No DIMM		
WLAN	Intel WiFi 6 AX201 & BT		
Bluetooth	V5.1		
Hard disk drives (internal)	PCIe-SSD, 512 GB M.2 NVMe module, SED		
	PCIe-SSD, 256 GB M.2 NVMe module, SED		
	PCIe-SSD, 2 TB M.2 NVMe module, SED		
	PCIe-SSD, 1 TB M.2 NVMe module, SED		
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity.  Accessible capacity may vary, also depending on used software.  Up to 20 GB of HDD space is reserved for system recovery		
Interface add on cards/components (optional)			
4G/ LTE (optional)	LTE Sierra Wireless EM7421 (Cat. 7)		
	LTE module Fibocom L850-GL(Cat.9)		
Display	33.8 cm (13.3-inch),IPS,Full HD,Anti-glare touchscreen,1,920 x 1,080 pixel,1000:1,400 cd/m²		
Multimedia			
Camera	Front: IR Cam (2 MP) supporting Windows Hello and secur Out camera: 5 MP with autofocus on top of C cover	eBIO with LED	

### Base unit

Base unit	LIFEBOOK U9311X black	LIFEBOOK U9311X red
General system information		
Chipset	Integrated in CPU	
Supported capacity RAM (min.)	8 GB	

General system information		
Supported capacity RAM (max.)	32 GB	
Memory slots	LPDDR4 (4266 MHz)	
Memory notes	8 GB / 16 GB / 32 GB onboard LPDDR4 (4266 MHz) Dual channel support	
LAN	10/100/1,000 MBit/s Intel® I219LM	
LAN notes	Intel vPro capable	
Integrated WLAN	Intel WiFi 6 AX201 with integrated BT	
BIOS version	UEFI Specification 2.7	
BIOS features	InsydeH2O BIOS	
Audio type	On board	
Audio codec	Realtek ALC255	
Audio features	2x digital array microphones, 2x built-in speakers (stereo)	
MIL-STD tested	Yes, selected MIL-STD-810H tests passed.  MIL-STD-810H test results are not a guarantee of future performance under identified test conditions.  Accidental damage is not covered under standard international limited warranty.	
Display		
Display notes	Wide-view high-bright LED display (for enhanced outdoo viewing). With magnesium display lid. Integrated ambient light sensor for automatic backlight adjustment to the working environment.	r Wide-view high-bright LED display (for enhanced outdoor viewing). With magnesium display lid. Integrated ambient light sensor for automatic backlight adjustment to the working environment.
Sensors	3-axis Accelerometer Gyroscope Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Magnetic Field Sensor Compass
Aspect ratio		16:9
Brightness - typical	400 cd/m <sup>2</sup>	$400 \text{ cd/m}^2$
Digitizer / Touch Technology	Wacom Digitizer for pen (AES) input plus capacitive 10 finger multi-touch screen	Wacom Digitizer for pen (AES) input plus capacitive 10 finger multi-touch screen
Ambient light sensor	Integrated	Integrated
Ambient light sensor notes	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight
Graphics		
Base unit	LIFEBOOK U9311X black	LIFEBOOK U9311X red
TFT resolution (HDMI)	up to 4,096 x 2,160 @ 60 Hz	up to 4,096 x 2,160 @ 60 Hz
Graphics brand name	Intel® Iris® Xe Graphics (with Dual channel memory)	Intel® Iris® Xe Graphics (with Dual channel memory)
Graphics features	3 Display Support (2 external, 1 internal) HDCP support DirectX® 12 OpenGL® 4.5	3 Display Support (2 external, 1 internal) HDCP support DirectX® 12 OpenGL® 4.5
Graphics notes	Shared memory depending on main memory size and operating system 3D accelerator	Shared memory depending on main memory size and operating system 3D accelerator
Interfaces		
DC-in	1	1
Audio: line-out / headphone	1 (combo port with Audio line-in)	1 (combo port with Audio line-in)
Audio: line-in / microphone	1 (combo port with Audio line-out)	1 (combo port with Audio line-out)
Internal microphones	2x digital array microphones	2x digital array microphones
USB 3.2 Gen 1 (5 Gbps) total	2x Type-A (1 with Anytime USB charge functionality)	2x Type-A (1 with Anytime USB charge functionality)
USB 4.0 Gen 3 (20 Gbps) total	2 x Type-C Intel® Thunderbolt™ 4 (with Power Delivery functionality), DP 1.4	2 x Type-C Intel® Thunderbolt™ 4 (with Power Delivery functionality), DP 1.4
USB Type-C	2 USB 4 Gen3 Thunderbolt™4, Power Delivery (15W), DP 1.4	2 USB 4 Gen3 Thunderbolt™4, Power Delivery (15W), DP 1.4
HDMI	1	1
Ethernet (RJ-45)	 1	1
culernet (KJ-45)	l	<u> </u>

Interferen				
Interfaces Mamorus card slats	1 (USH II) SD 4.0 standard	1 // IC	H II) CD 4 0 ct	andard
Memory card slots	1 (USH-II) SD 4.0 standard SD/microSD card: 2GB	· ·	H-II) SD 4.0 sta icroSD card: 2	
	SDHC/microSDHC card: 32GB		:/microSDHC	
	SDXC/microSDXC card: 2TB		/microSDXC o	
	Speed Class: up to UHS-II (156MB/s)	Speed	d Class: up to	UHS-II (156MB/s)
SmartCard slot	1	1		
SIM card slot	1 (Nano-SIM, only for models with inte module)	grated 4G/LTE 1 (Na modu		for models with integrated 4G/LTE
Docking connector for Port Replicator	USB Type-C Portreplicator	USBT	ype-C Portre	olicator
Kensington Lock support	1	1		
Port Replicator interfaces (optional)				
	Thunderbolt™ 4 PR	USB Type-C PR		Thunderbolt™ 3 PR
DC-in	1 (20V/170W required)	1 (19V/90W required)		1 (20V/170W required)
Power on switch	1	1		1
Audio: comments	1 Combo jack for headset usage	1 Combo jack for headse	t usage	1 Combo jack for headset usage
DisplayPort	2 (up to 2560 x 1600), DP 1.4	1 (up to 2560 x 1600)		2 (up to 2560 x 1600)
VGA		1 up to 1920×1200 @ 60h		
		depending on FJ mobile		
HDMI text	1	1		1
Interface Notes	2x Type-A - 5V/0.9A, 4.5W	3x Type-A - 5V/0.9A, 4.5W	1	2x Type-A - 5V/0.9A, 4.5W
	1x Type-A - 5V/2.4A, 12W	1x Type-C - 15W		1x Type-A - 5V/2.4A, 12W
	2x Type-C - 5V, 1.5A, 4.5W charging	1x Type-C - Up to 60 W (P		2x Type-C - 5V, 1.5A, 4.5W charging
	port 1x Type-C - TBT4 up to 60 W (PD v2.0-	power output to client or	4.5W input	port 1x Type-C - TBT3 up to 60 W (PD v2.0-
	1.1), 5-20V, 3.0A upstream (PC)			1.1), 5-20V, 3.0A upstream (PC)
	1x Type-C - TBT4 up to 15 W (PD			1x Type-C - TBT3 up to 15 W (PD
	v2.0-1.1), 5V, 3.0A downstream, power			v2.0-1.1), 5V, 3.0A downstream, power
	output to client			output to client
Kensington Lock support	1	no		1
Notes	RJ-45:10/100/1000 MBits/s LAN	1 RJ45 (10/100/1000)		RJ-45:10/100/1000 MBits/s LAN
	WoL from S3 state	WoL from S3 state	1.	WoL from S3 state
	WoL from S4 / S5 / G3 state depending on Fujitsu mobile client	WOL from S4 / S5 / G3 de Fujitsu mobile client	pending on	WoL from S4 / S5 / G3 state depending on Fujitsu mobile client
			ted FJ mobile	PXE launching for dedicated FJ mobile
	clients	clients	tea 13 mobile	clients
	Set the MAC address by the user	Set the MAC address by t	he user	Set the MAC address by the user
	MAPT from 10th gen	MAPT from 9th gen		MAPT from 9th gen
Keyboard and pointing devices				
	Backlight keyboard w/o touchstick			
	Number of keyboard keys: 85, Keyboar	rd pitch: 19 mm, Keyboard	stroke: 1.5 m	m
	Multi gesture touchpad with integrate	d mouse button functiona	ality	
	Touchscreen			
	Tablet Pen (AES), stored in pen garage			
NAP I I I I I				
wireless technologies			2x dual band for WLAN, 2x for LTE, Bluetooth shared with WLAN	
Wireless technologies Antennas	2x dual band for WLAN, 2x for LTE, Blue	etooth shared with WLAN		
	2x dual band for WLAN, 2x for LTE, Blue v5.1	etooth shared with WLAN		
Antennas Bluetooth		etooth shared with WLAN		
Antennas Bluetooth Integrated WLAN	v5.1			
Bluetooth Integrated WLAN WLAN encryption	v5.1 Intel WiFi 6 AX201 with integrated BT	cess)		
Antennas Bluetooth Integrated WLAN WLAN encryption WLAN notes	v5.1 Intel WiFi 6 AX201 with integrated BT WPA/WPA2/WPA3 (Wi-Fi Protected Acc	cess)		
Antennas Bluetooth Integrated WLAN WLAN encryption WLAN notes	v5.1 Intel WiFi 6 AX201 with integrated BT WPA/WPA2/WPA3 (Wi-Fi Protected Acc Import and usage according to countr	ress) y-specific regulations. y-specific regulations.		
Antennas Bluetooth Integrated WLAN WLAN encryption WLAN notes LTE/UMTS/GPS notes	v5.1 Intel WiFi 6 AX201 with integrated BT WPA/WPA2/WPA3 (Wi-Fi Protected Acc Import and usage according to countr Including GPS functionality Import and usage according to countr	cess) y-specific regulations. y-specific regulations. d with 4G/LTE)		
Antennas	v5.1 Intel WiFi 6 AX201 with integrated BT WPA/WPA2/WPA3 (Wi-Fi Protected Acc Import and usage according to countr Including GPS functionality Import and usage according to countr LTE Connection Manager (if configured	cess) y-specific regulations. y-specific regulations. d with 4G/LTE)		

Power supply			
AC adapter	19 V / 65 W (3.42 A)#20 V / 65 W (3.25 A) Type	C	
Notes	· · ·	90W AC Adapter for usage with Type C Port Replicator	
Rated voltage range	100 V - 240 V (AC Input)		
Rated frequency range	50 Hz - 60 Hz		
1st battery options	Lithium polymer battery 4-cell, 50 Wh		
1st battery			
Battery features	Quick Charge: 80% in 1h		
Runtime 1st battery	11 h		
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2018. Refer to www.bapco com for additional details.  The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.		
Noise emission			
Noise emission	Please refer to the Eco Declaration	Please refer to the Eco Declaration	
Dimensions / Weight / Environmental			
Dimensions (W x D x H)	309 x 214.8 x 16.9 mm		
ZSIISISIIS (IT N.D.N.II)	12.18 x 8.41 x 0.62 inch		
Weight	1,015 kg		
Weight (lbs)	2,23 lbs		
Weight notes	Weight may vary depending on actual config	uration	
Operating ambient temperature			
Operating ambient temperature  Operating relative humidity	5 - 35 °C (41 - 95 °F); Packed -10 - 60 °C (14 - 140 °F)  Running: 20 - 80% (relative humidity); Packed: 20 - 80% (relative humidity)		
Compliance	naming. 20 00% (relative naminary), racket	20 50% (Clutive numbers)	
Product	LIFEBOOK U9311X		
Global		on)	
	TCO Certified 8.0 (depending on configuration https://sp.ts.fujitsu.com/sites/certificates	)II)	
Compliance link	nttps://sp.ts.rujitsu.com/sites/certificates		
Additional Software			
Additional software (preinstalled)		nent utility) soft® Office 365 customers. Buy Microsoft Office.)	
Additional software (optional)	Recovery DVD for Windows® Drivers & Utilities DVD (DUDVD) optional CyberLink PowerDVD BD (playback software CyberLink PowerDVD DVD (playback softwar CyberLink YouCam (webcam software) Nero (backup and burning software)		
Manageability			
Manageability technology	DeskUpdate Driver management PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN) Intel® vPro™ technology iAMT 14.0 (depending on processor)		
Manageability software	DeskView Client DeskView Instant BIOS Management		

Manageability		
DeskView components	Inventory Management	
	BIOS Management	
	Driver Management	
	Security Management	
	Alarm Management	
Supported standards	WMI (Windows Management Instrumentation)	
	PXE (Preboot Execution Environment)	
	DMI (Desktop Management Interface)	
	SMBIOS (System Management BIOS)	
	WBEM (Web Based Enterprise Management)	
	CIM (Common Information Model)	
	BootP (made4you)	
Manageability link	http://www.fujitsu.com/fts/manageability	
Security		
Physical Security	Kensington Lock support	Kensington Lock support
System and BIOS Security	Absolute Persistence® technology capable BIOS	Absolute Persistence® technology capable BIOS
,	EraseDisk (optional)	EraseDisk (optional)
	Optional: Trusted Platform Module (TPM 2.0)	Optional: Trusted Platform Module (TPM 2.0)
User Security	Hard disk password	Hard disk password
	User and supervisor BIOS password	User and supervisor BIOS password
	Workplace Protect (secure authentication solution)	Workplace Protect (secure authentication solution)
	Embedded fingerprint sensor (optional)	Embedded fingerprint sensor (optional)
		E
	Embedded PalmSecure™ sensor (optional)	Embedded PalmSecure™ sensor (optional)

Warranty	
Warranty period	2 years (for countries within EMEIA)
Warranty type	Bring-in Service / Collect & Return Service (depending on country)
Warranty Terms & Conditions Product Support Services - the perf	http://www.fujitsu.com/warranty ect extension
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	5 years after end of product life
Service Weblink	http://www.fujitsu.com/emeia/products/product-support-services/

### **Recommended Accessories**

USB Type-C Port Replicator 2



Connect to your peripherals. Adapt to the task on demand. The universal USB Type-C connection helps you to get your peripheral devices connected easily. Enhance your USB connection options, connect your displays via HDMI, DisplayPort or VGA and charge your device without an additional charger.

Weight: 334 g, Dimensions: 219 x 75 x 22.9 (front) - 26.0 (back) mm, including 90W AC adapter and Type C cable

Order Code: S26391-F3327-L100

## Fujitsu recommends Windows 10 Pro for business.

Thunderbolt™ 3 Port Replicator



One cable, many capabilites - Connect, save space, and keep your desk tidy. With Thunderbolt™ 3 you can connect almost everything with only on cable and in highspeed. Enhance your USB connection options, connect your displays via Thunderbolt™ 3, HDMI, DisplayPort and charge your device without an additional charger. Thunderbolt™ 3 allows you to connect even highspeed devices in a most convenient way.

Weight: 440 g, Dimensions: 239 x 80 x 26 mm, including 170W AC adapter and TBT cable

Order Code: S26391-F3357-L100

USB Type-C AC Adapter



Recharge your notebook or tablet at work, at home or on the road with this Order Code:
USB Type-C power source easily.
S26391-F3326-L502

AES Pen with replacement stylus tips



Take your creativity to the next level, with the most natural pen experience Order Code: with the AES Pen with replacement stylus tips. With pen nibs that are very thin, you can experience the writing and signing behavior of an ink pen.

Car Adapter USB-C-QC



One Car Adapter fits all.

Independent of your mobile device charging method this car adapter will fulfill all major requirements and standards for fast charging vendorbrand-independent notebooks and all mobile devices. The Car Adapter USB-C-QC supports USB PD with PPS, Quick Charge (QC), Apple- and Samsung charge.

Order Code: S26391-F2613-L630

### More information

### Fujitsu products, solutions & services

In addition to FUJITSU Tablet LIFEBOOK U9311X, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

### Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products www.fujitsu.com/global/products/computing/

Software www.fujitsu.com/software/

### More information

Learn more about FUJITSU Tablet LIFEBOOK U9311X, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.

www.fujitsu.com/emeia/products/computing/pc/tablets

#### Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment.

Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT

Please find further information at http://www.fujitsu.com/global/about/environment



### Copyrights

All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use. html

Copyright 2021 Fujitsu Technology Solutions

#### Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner.

### Contact

Fujitsu Technology Solutions GmbH Website: www.fujitsu.com 2021-02-26 EM-EN All rights reserved, including intellectual property rights. Designations may be trademarks and/or copyrights of the respective owner, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu.com/emeia/resources/navigation/terms-of-use.html
Copyright 2021 Fujitsu Technology Solutions GmbH