

Overview

Models

HP DX115 Removable HDD Frame/Carrier	FZ576AA
HP DX115 Removable HDD Carrier	NB792AA
HP DX115 Carrier with 160GB SATA HDD	FZ577AA

Introduction

The HP DX115 Removable Enclosure is a rugged drive carrier and receiving frame for internally mounting a SATA or SAS hard drive into a 5.25 inch optical drive bay in an HP Workstation.

The DX115 supports a SAS (Serial Attached SCSI) or SATA (Serial ATA) 3 Gb/s drive.

- HP DX115 Removable HDD Frame/Carrier (FZ576AA)-- A receiving frame and carrier for a SAS or SATA 3 Gb/s disk. The receiving frame installs in one of the 5.25" optical bays in the workstation. The carrier holds the HDD and has a quick release handle for insertion/removal. You can install any HP supported 3.5" disk in the carrier. SATA disks are only supported when connected to the workstation's onboard SATA controller.
- HP DX115 Removable HDD Carrier (NB792AA) -- Use this carrier for adding spare or additional drives. Hard Drive purchased separately.
- HP DX115 Carrier with 160 GB SATA HDD (FZ577AA) -- A carrier with a 160 GB SATA 7200 HDD pre-installed.

Performance and Features

- Enclosure with centered drive carrier ensures no interference with the workstation bezel Drive spin/power up/down button Power, spin & fan failure indicator Drive activity indicator (system-dependent) "Soft Start" circuitry & anti-static device protection Cable-less drive connector Rugged construction; drive is protected in the event of physical trauma Mating connectors provide 25K insertion rating for multiple insertions and removals Integrated fan assures proper drive cooling Key lock functions independently from drive power

Compatibility

Up to two DX115 enclosures are supported with the HP xw4600, xw6600, xw8600, xw9400, Z400 and Z800 Workstations. The HP Z600 workstation supports one DX115 enclosure.

Compatible Optical Bay Location marked via X	xw4600	xw6600		XW8600 xw9400	
	Z400		Z600		Z800
Top Bay	X	X*		X	
Middle Bay	X	N/A**	N/A**	X	X
Bottom Bay		X	X	X	X

*DX115 fits in Top Bay if Hood Lock Solenoid (DY305AV or DE618A) is not installed.

** Not Applicable, no middle bay present

Service and Support

The HP DX115 Removable Enclosure products have a one-year limited warranty or the remainder of the warranty of the HP product in which it is installed. Technical support is available seven days a week, 24 hours a day by phone, as well as online support forums. Parts and labor are available on-site within the next business day. Telephone support is available for parts diagnosis and installation. Certain restrictions and exclusions apply.

Technical Specifications

Interface Type	Compatible with SAS or SATA controllers
Dimensions (WxHxD)	147.6mm W x 41.1mm H x 205mm L (5.81" W x 1.62" H x 8.08" L)
Weight	Frame and Carrier: 1.73 kg (3.8 lbs) Carrier: 0.45 kg (1 lbs)

© Copyright 2010 Hewlett-Packard Development Company, L.P.
The information contained herein is subject to change without notice.

The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.